

Agrofarm 420 DT

Engine

Deutz 2012 Tier 3 Diesel Engine
4 Cyl/4038cc Turbocharged /Intercooled
Electronically Controlled
Liquid/Oil Cooled
High pressure Diesel injection
102 hp @ 2300 rpm (2005/25/CE)
Torque 380nm
100% Bio Diesel Compliant
Engine Speed Programming
Side exhaust
160lt Fuel Capacity

Transmission

20/20 forward/reverse gears
Heavy duty 13" dry Cerametallic clutch
Synchronized forward/reverse shuttle
Shuttle lever located left hand side
Creep Std
Front Wheel Assist
4 Wheel Independent Braking
100% Front & Rear Diff Lock- Push button
40 km/h Road speed

PTO

Independent wet multidisc clutch
4 Speed PTO 540/540E- 1000/1000E
Push Button control

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
420/70R24 Front 480/70R34 Rear
Front weight frame and tow hitch



Operator Environment

4 Post Hi visibility Air Conditioned Cab
Ergonomic Controls
Multi Function Digital Dash
Super Deluxe Air Seat
Deluxe Cabin Work Light Package
Telescopic Mirrors
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
56 L/min Hyd a Rear Remotes
Separate 44L/min Steering Pump
2 Sets of Remotes
Mechanical Linkage c/w position & draft controls
External Mechanical Raise and Lower
Cat 2 Ball Ends
5100 kg lift capacity

Weights & Dimensions

Wheelbase	2320mm
Length	3950mm
Total Height	2580mm
Total Weight	4050kg



K C Farm Equipment

28 Three Chain Road
SOUTH LISMORE NSW 2480
Ph: 02 6622 8122 Fax: 02 6622 8875
www.farm-equipment.com.au