

Agrofarm 420 ROPS

Engine

Deutz 2012 Tier 3 Diesel Engine
4 Cyl/4038cc Turbocharged
Electronically Controlled
Liquid/Oil Cooled
High pressure Diesel injection
102 hp @ 2300 rpm (2005/25/CE)
Torque 380nm
100% Bio Diesel Compliant
Engine Speed Programming
Side exhaust
160lt Fuel Capacity

Transmission

40/40 forward/reverse gears
Wet clutch Powershuttle
2 Speed Powershift
Comfort Clutch
Creep Std
Front Wheel Assist
4 Wheel Independent Braking
100% Front & Rear Diff Lock
40 km/h Road speed

PTO

Independent wet multidisc clutch
4 Speed PTO 540/540E- 1000/1000E
Push Button control
Interchangeable PTO Shaft Function

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
420/70R24 Front -480/70R34 Rear
Front Weight Frame



Operator Environment

2 Post ROP Frame
Flat Floor ISO Mounted Platform
Rubber Floor Mat
Ergonomic Controls
Telescopic and Tilting Steering Wheel
Multi Function Digital Dash
Deluxe PVC Mechanical Seat
Sun Canopy
Telescopic Mirrors
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
56 L/min Hyd a Rear Remotes
Separate 44L/min Steering Pump
2 Sets of Remotes
Mechanical Linkage c/w position & draft controls
External Raise & lower on Rear Fender
Cat 2 Hook Ends
5100 kg lift capacity

Weights & Dimensions

Wheelbase	2320mm
Length	3950mm
Total Height	2580mm
Total Weight	3650kg



K & C Farm Equipment

28 Three Chain Road
SOUTH LISMORE NSW 2480
Ph: 02 6622 8122 Fax: 02 6622 8875
www.farm-equipment.com.au