

# RX7620 UTILITY TRACTOR

## STANDARD TRACTOR SPECIFICATIONS

### ENGINE

Daedong 4F243T-TPC3 CRDI  
Liquid Cooled 4 Cylinder Diesel Turbo  
2435cc Displacement  
76 HP @ 2600 rpm  
95 Litre fuel Tank Capacity

### TRANSMISSION

Power Shuttle  
4 Main Gear x 6 Range Gear Shift  
24F X 24R Speed  
4 Wheel Drive with Wet Multi Disk Engagement

### HYDRAULICS & LINKAGE

Implement Pump 41.6 lpm  
Power Steering Pump 31.2 lpm  
Total Hydraulic Flow 72.8 lpm  
Category 2 Three Point Linkage  
Cassette Type Lower link  
2256kgs Maximum rear Lift Capacity  
Clevis Type Rear Draw Bar  
Standard 2 Pair Hydraulic rear remotes  
Hydraulic Power Steering

### POWER TAKE OFF

Independent  
540 / 750 rpm  
SAE 1-3/8, 6 Spline

### TYRES

AG Tyre Front 11.2 - 24  
Rear 16.9 - 30

### BRAKES

Wet Disk

### OPERATOR ENVIRONMENT

High Quality Fully Adjustable Seat  
with Arm Rests and Backrest  
Adjustable Steering Wheel and Instruments  
Flat Operator Deck

### CABIN

Deluxe Cabin with A/C and Heating  
Tinted Glass, CD Radio  
Front and Rear Wipers  
Internal / External Air Exchanger Filters  
Refrigerator/ Heating Cabinet

### TRAVEL SPEEDS

Forward 1.63 - 38.82kph  
Reverse 1.61 - 38.17kph

### DIMENSIONS

Overall Length inc 3PL 3480mm  
Overall Width min tread 1960mm  
Overall Height (Cab) 2655mm  
Overall Height (ROPS) 0000mm  
Wheelbase 2130mm  
Ground Clearance 440mm  
Weight with Cab/ AG 2975kg  
Weight ROPS/ AG 2530kg

### MODEL

RX7620 ROPS  
RX7620 CAB

### OPTIONS

KL705 Loader with 4 in 1 bucket  
Rear Counter Balance Weight Box 650kg  
Pallet Forks to fit KL1595 Loader  
Bale Forks to fit KL1595 Loader

### ASSEMBLY & FITMENT

Loader Fitment Charge ROPS only